## **TECHNICAL DATA SHEET DECORATIVE PANELS**





REFERENCE

PD001\_LLIS

**DESCRIPTION** 

Plain, no machining





**FEATURES** 

Materials

♦ Damp-proof MDF

♦ Wood

◆ Damp-proof mass tinted MDF

♦ Acrylic resin

Max. thickness(mm)

♦ 16/22/47 mm (MDF)

♦ 12,3 mm (acrylic resin)

For other materials and thickness, contact with DECUSTIK

Max. depth (mm)

Fireproofing

♦ D - s2, d0 (MDF)

according to EN 13501-1

♦ C - s1, d0 (acrylic resin)

For other grades and materials, contact with DECUSTIK

Density (kg/m<sup>2</sup>)

♦ 12/16,5/35,3 (MDF)

♦ 21,5 (acrylic resin)

Sizes

◆ Standard dimension 2400x1200mm (MDF)

♦ Max. dimension 3000x1500mm (MDF)

For other dimensions and materials, contact with DECUSTIK

Finishing

♦ Ecru

♦ White lacquered/color (2)(3)(5)-according to RAL colour chart

♦ Varnished (2)(3)

◆ Metallic lacquered (²)(³)(⁵) - according to RAL colour chart

◆ Polylaminated

◆ Polished (<sup>4</sup>)

Edge machining

♦ Viewed ♦ Grooving

Dovetailing

## **APPLICATIONS**

- ♦ Wall covering
- ◆ Ceiling
- ♦ Furniture accessories

## **ACCESSORIES FOR ASSEMBLY**

Edge profiles

◆ Edge profiles, corners and ends (wall covering)

◆ Trims (wall covering and ceilings)

♦ 45° angle

Fixing system

◆ Ceiling: standard system for semi-hidden and hidden edge machining

♦ Wall covering: standard system according to edge machining

- viewed
- grooving
- dovetailing

## **NOTES**

- (1) Values corresponding to indicated thickness without additional elements nor attachments
- (2) Available in normal and fire-proof quality
- (3) Not applicable to acrylic resins
- (4) Applicable only to acrylic resins
- (5) Matt, satin or glossy finishing